DART SERVICE INSTRUCTION
TO AMEND INSTALLATION INSTRUCTIONS IIN-D212-664 REV. G AND EARLIER AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D212-664 REV. 8 AND EARLIER

REF TCCA STC: SH01-9 REF FAA STC: SR01298NY REF EASA STC: EASA.IM.R.S.01304

Purpose:


Clarify the graphics showing the aircraft cap assemblies in IIN-D212-664 Rev. G and earlier and ICA-D212-664 Rev. 8 and earlier.

## Discussion:

The cap assemblies shown in applicable figures are only meant to be a pictorial reference and it is not Dart's intention to impose any changes in shape or form to the aircraft cap assemblies and their installation when installing the Dart crosstubes.

## Conclusion:

Installers should be using the existing cap assemblies and associated hardware and shimming procedures that are approved for their aircraft when installing the Dart crosstubes.



## TYPICAL FWD CROSSTUBE SECTION VIEW

(AFT CROSSTUBE SECTION VIEW SIMILAR)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION **BRANCH** DAO # 01-O-01

DATE: CERT. NO.: ISSUE NO .:

A	NEW IS	ISSUE				12.07.17
REV.				DESCRIPTION		DATE
DESIGN		上路		DART AEROSPACE LTD		
DRAWN			3	HAWKESBURY, ONTARIO, CANADA		
CHECKED		(1)	)	DRAWING NO.		REV. A
MFG. APPR.		N/A	}	DSI 9627		SHEET 1 OF 1
APPROVED		4		TITLE		SCALE
DE APPR.		-//	_	INSTALL CLARIFICAT	ION	NTS
DATE 12.07.17 COPYRIGHT © 2012 BY DART AEROSPACE LTD  THIS DOCUMENT IS PRINCIPLE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THA  NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITH  WRITTEN PERMISSION FROM DOAT AEROSPACE LTD.						S CONDITION THAT IT IS